

# HGUIDE I700 MEMS IMU

The HGuide i700 is a proven low-SWaP, near-navigation grade MEMS IMU that requires no export license and is fully calibrated across a wide temperature range.



## AIR

- Class 3 UAV
- Aerial Survey
- EI/IR Pods

## LAND

- UGV Navigation
- Mobile Survey
- Pipeline Inspection

## SEA

- Surface Heave and Navigation
- Marine Survey
- Underwater Vehicles

## HONEYWELL INERTIAL ADVANTAGE

Honeywell Aerospace is a global leader in high performance inertial measurement units (IMUs), delivering precise navigation, stabilization, and control across a wide range of applications.

Our extensive portfolio of inertial sensors and navigators serves diverse sectors within the aerospace, defense, and industrial markets.

Whether MEMS, FOG, or RLG-based, Honeywell IMUs offer exceptional accuracy and reliability— even in the most demanding environments.

Our globally recognized IMU manufacturing capabilities are backed by ISO 9001:2015 and AS9100D certifications, with over 1 million tactical-grade IMUs delivered to date.

## THE HGUIDE I700 ADVANTAGE

- Best-in-Class MEMS IMU with unmatched performance for its size and price point
- Proven reliability and ruggedness - engineered for dependable operation throughout the unit's lifecycle
- Low SWaP, Cost-Effective near-nav-Grade IMU
- No Export License Required. ECCN = 7A994
- World-Class inertial sensor development - includes advanced calibration and compensation capabilities
- Higher dynamics served by [HG3900](#)

| GENERAL                               |                             |
|---------------------------------------|-----------------------------|
| Gyro Operating Range (°/sec)          | 400                         |
| Accelerometer Operating Range (G)     | 20                          |
| Output Data Rate (inertial data) (Hz) | 600 /100, Standard          |
| Update rate (roll & pitch)            | N/A                         |
| Start-up time to full performance     | 5 seconds, standard         |
| Output Data Protocol                  | ASYNCR                      |
| Calibration                           | Over Full Temperature Range |
| Bandwidth, -90°/-3 dB (Hz)            | 70/180                      |

| MECHANICAL                   |                                 |
|------------------------------|---------------------------------|
| Size (mm)                    | 75 x 75 x 79 (not inc. tabs)    |
| Weight (g)                   | 907                             |
| Seal (IP Rating)             | Semi-Hermetic                   |
| Materials/Construction       | Machined and Anodized Aluminium |
| External Connector           | Samtec TMM Series (TMM-115)     |
| Recommended Mating connector | CLT series (CLT-115)            |

| GYRO PERFORMANCE<br>PARAMETER                               | Performance<br>(Factory Fresh) | Performance<br>(Full Life - 10 years) |
|---|--------------------------------|---------------------------------------|
|   | I700 BA                        | I700 BA                               |
| Gyro Bias In-Run Stability (RMS) (°/hr 1σ)                  | 0.06                           | 0.08                                  |
| Gyro Bias Repeatability (turn-on to turn-on, RMS) (°/hr 1σ) | 0.15                           | 0.5                                   |
| Gyro Noise – ARW (°/√hr)                                    | 0.008                          | 0.015                                 |
| Gyro Scale Factor Repeatability (ppm, 1σ)                   | 200                            | 300                                   |
| Gyro Scale Factor Static G-Sensitivity (ppm/g, 1σ)          | 50                             | 50                                    |
| Gyro Scale Factory Linearity Error (ppm 1σ)                 | 400                            | 1000                                  |
| Gyro Axis Misalignment (μrad 1σ)                            | 100                            | 100                                   |
| Vibration Rectification Error (°/hr)                        | 1                              | 1                                     |

| ACCEL PERFORMANCE<br>PARAMETER                             | Performance<br>(Factory Fresh) | Performance<br>(Full Life - 10 years) |
|--|--------------------------------|---------------------------------------|
|  | I700 BA                        | I700 BA                               |
| Accel Bias In-Run Stability (RMS) (mg 1σ)                  | 0.012                          | 0.02                                  |
| Accel Bias Repeatability (turn-on to turn-on, RMS) (mg 1σ) | 0.5                            | 2                                     |
| Accel Noise – VRW (m/s/√hr)                                | 0.02                           | 0.02                                  |
| Accel Scale Factor Accuracy (ppm 1σ)                       | 100                            | 100                                   |
| Accel Scale Factory Nonlinearity (ppm 1σ)                  | 8                              | 8                                     |
| Accel Axis Misalignment (μrad 1σ)                          | 300                            | 300                                   |
| Vibration Rectification Error (mg)                         | 0.12                           | 0.5                                   |

## ELECTRICAL

|  |                                     |
|--|-------------------------------------|
| Input Supply Voltage (nominal & min/max) | +5 VDC and +15VDC                   |
| Power Consumption (Watts, typical & max) | < 6 Watts (Start), <2.5W (Run)      |
| Data Interfaces                          | Async RS422                         |
| ESD Compliance (rating & list of tests)  | ISO 10605:2008/Amd 1:2014 Unpowered |
| EMC Compliance (list of tests)           | MIL-STD-461G                        |


## ENVIRONMENTAL

|                                  |   |
|----------------------------------|---|
| Mechanical Shock profiles tested | 50G SRS   |
| Vibration profiles tested        | 3.9 gRMS 10-2000Hz random vibration standard          |
| Operating Temperature            | -55°C to +85°C  |
| Storage Temperature              | -55°C to +85°C  |
| Humidity                         | DO-160G Section 6, Category B                         |
| MTBF                             | 50,000 hour, MIL-HDBK-217F AIC at 25°C                |
| Lifetime – operational           | 500 hrs minimum without recalibration; 10 years total |
| Lifetime – storage               | 10 years minimum                                      |

## CONNECTIONS

| PIN | LEGEND   | DESCRIPTION             | PIN | LEGEND     | DESCRIPTION                     |
|-----|----------|-------------------------|-----|------------|---------------------------------|
| 1   | +5VDC    | +5VDC Power Input       | 16  | Reserved   | User no Connect                 |
| 2   | +15VDC   | +15VDC Power input      | 17  | Reserved   | User no Connect                 |
| 3   | +5V GND  | +5VDC Power Return      | 18  | Reserved   | User No Connect                 |
| 4   | +15V GND | +15VDC Power Return     | 19  | Reserved   | User No Connect                 |
| 5   | CGND     | Chassis Ground          | 20  | SER_DATA_L | Serial Data Output - Low        |
| 6   | Reserved | User no Connect         | 21  | Reserved   | User no Connect                 |
| 7   | GP_CLK_H | Data Sync Output - High | 22  | SER_DATA_H | Serial Data Output - High       |
| 8   | Reserved | User no Connect         | 23  | RESET_N    | Reset Input - Active Low        |
| 9   | GP_CLK_L | Data Sync output - Low  | 24  | IBIT_N     | IBIT Command Input - Active Low |
| 10  | Reserved | User no Connect         | 25  | Reserved   | User no Connect                 |
| 11  | Reserved | User no Connect         | 26  | Reserved   | User no Connect                 |
| 12  | Reserved | User no Connect         | 27  | Reserved   | User no Connect                 |
| 13  | Reserved | User No Connect         | 28  | Reserved   | User No Connect                 |
| 14  | Reserved | User No Connect         | 29  | Reserved   | User No Connect                 |
| 15  | Reserved | User No Connect         | 30  | Reserved   | User No Connect                 |

Standard units - for more details see manual or contact Honeywell.





## HOW TO BUY

For high volume OEM customers, we recommend purchasing directly from Honeywell via our online portal.

For small-volume orders or for customers who need faster delivery and local support, please contact one of our authorized channel partners listed here.

### HGUIDE I700 ORDERING AND ACCESSORIES

| PRODUCT        | ORDERING PART NUMBER | DESCRIPTION               |
|----------------|----------------------|---------------------------|
| HGuide i700 BA | 68910700-BA02        | Standard B-Grade i700 IMU |

### Tech. and Sales Support

[resilient.navigation@honeywellaerospace.com](mailto:resilient.navigation@honeywellaerospace.com)

### For more information

[aerospace.honeywell.com/HGuide](https://aerospace.honeywell.com/HGuide)

### Honeywell Aerospace

1944 East Sky Harbor Circle

Phoenix, AZ 85034

[aerospace.honeywell.com](https://aerospace.honeywell.com)

The HGuide i700 is designed and built at a Honeywell facility in the USA.

It has an ECCN of 7A994 and is generally available without an export license.

This document does not contain EAR controlled technology or ITAR controlled technical data.

N61-3307-000-000 | 03/26  
© 2026 Honeywell International Inc.

**THE  
FUTURE  
IS  
WHAT  
WE  
MAKE IT**

**Honeywell**